

Model: [1541.44101](#)
15 FRAME PLUNGER PUMP - TEG



Specs

Max Flow:	18 gpm
Min Pressure:	100 psi
Max Pressure:	1200 psi
Inlet Port Size:	1"NPT
Discharge Port Size:	3/4"NPT
RPM:	1100
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a positive displacement (PD), reciprocating, triplex (three plunger rods) plunger pump constructed of 316 stainless steel manifolds, 316 stainless steel valve assemblies, solid ceramic plungers and FPM seals and o-rings. This pump has been designed to handle Triethylene Glycol (TEG) up to 240 degrees F (116 degrees C) the most common method for removing water from natural gas. Our electric/engine driven TEG pump product line has been field proven in the most rigorous dehydration conditions and will meet Hazardous Air Pollutants (HAP) compliance and lower regulatory costs. (see 1540E44101 for brass model)

Datasheet: [1540E.44101-1541.44101 Data Sheet](#)

Service Manual: [15-25 Frame Plunger Service Manual](#)

Accessories:

Regulator

 [7021.100](#) SS Pressure Regulator

Unloader

 [7531](#) Multiple Gun Pressure Unloader

Relief / Pop-Off Valve

 [7531.100](#) SS Pressure Relief Valve

Pressure Gauge



[6073](#) Pressure Gauge

Pulsation Dampener

 [6013](#) Prrrrr-O-Lator-Rechg-FPM