



Model: [2520](#)
25 FRAME PISTON PUMP

Specs

Max Flow:	25 gpm
Min Pressure:	100 psi
Max Pressure:	800 psi
Inlet Port Size:	1.25
Discharge Port Size:	1
RPM:	772
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex (three piston rods) positive displacement, reciprocating, piston pump, constructed with chrome-plated brass manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction.

Datasheet: [1520-2520 Data Sheet](#)

Service Manual: [Piston Pump Service Manual](#)

Accessories:


Oil

	6107	Crankcase Oil
---	----------------------	---------------

Regulator

	7021	Pressure Regulator
---	----------------------	--------------------

Unloader

	7590	Multiple Gun Pressure Unloader
---	----------------------	--------------------------------

Relief / Pop-Off Valve

	7595	High Flow Relief Valve
---	----------------------	------------------------

Pressure Gauge

	6086	Pressure Gauge
---	----------------------	----------------

Pulsation Dampener

	6010	Prrrrr-O-Lator-Rechg-NBR
---	----------------------	--------------------------

Captive Acceleration Tube

	714500	Captive Acceleration Tube
---	------------------------	---------------------------


Inlet Filter



[7107.7](#)

Inlet Filter

Flexible Inlet Hose



[990843](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990833](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor

Other



[34334](#)

Oil Drain Kit