



**Model: [2530E](#)
25 FRAME PLUNGER PUMP**

Specs

Max Flow:	25 gpm
Min Pressure:	100 psi
Max Pressure:	1000 psi
Inlet Port Size:	1.25
Discharge Port Size:	0.75
RPM:	1025
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a high performance mid-size triplex (three plunger rods) positive displacement, reciprocating, plunger pump. It has a forged brass manifold, 304SS valve assemblies, concentric, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. It also features a durable blue 2 mil epoxy paint treatment on the crankcase, rear cover and bearing covers and a special liquid gasket between the crankcase and manifold to seal out moisture. This high capacity plunger pump is suitable for automatic car wash systems, multi-gun and multi-nozzle cleaning, multi-drop high pressure cleaning systems.

Datasheet: [2530-2530E-2531-2537 Data Sheet](#)

Service Manual: [25 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7022](#)

Pressure Regulator

Relief / Pop-Off Valve



[9940](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6010](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube

Inlet Filter



[7107.7](#)

Inlet Filter


Flexible Inlet Hose



[990843](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990837](#)

Flexible Discharge Hose

LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor