



The Pumps with Nine Lives



Model: [280](#) 3 FRAME PISTON PUMP

Specs

Max Flow:	3 gpm
Min Pressure:	100 psi
Max Pressure:	1000 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1330
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex [three piston rods] positive displacement, reciprocating, piston pump, constructed with chrome-plated brass manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction.

Datasheet: [280-281-290-291 Data Sheet](#)

Service Manual: [Piston Pump Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7001](#)

Pressure Regulator

Unloader



NO IMAGE AVAILABLE

[7500S](#)

Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[30960](#)

Pop-Off Valve

Pressure Gauge



[6086](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube


Inlet Filter



[7104.4](#)

Inlet Filter


Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit