



The Pumps with Nine Lives

### Model: [340B](#) 5 FRAME PLUNGER PUMP



#### Specs

Max Flow:	4 gpm
Min Pressure:	100 psi
Max Pressure:	1800 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1725
Drive Type(s):	Belt
Material:	Brass (BB)

#### Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of special brass manifolds, 304 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Bunea-N) seals and o-rings. The 1725 RPM permits multiple drive options including direct drive, flexible coupling, clutch or belt drive.

Datasheet: [310-340-350-310B-340B-350B-310S-340S-350S Data Sheet](#)

Service Manual: [5-15 Frame Plunger Service Manual](#)

#### Accessories:

##### Oil



[6107](#)

Crankcase Oil

##### Regulator



[7002](#)

Pressure Regulator

##### Unloader



[7500S](#)

Pressure Sensitive Regulating Unloader

##### Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

##### Pressure Gauge



[6088](#)

Pressure Gauge

##### Pulsation Dampener



[6029](#)

Prrrrr-O-Lator-Rechg-NBR

##### Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

### Inlet Filter



[7104](#)

Inlet Filter



[7104.4](#)

Inlet Filter

### Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

### Other



[34334](#)

Oil Drain Kit