



**Model: [3517](#)**  
**35 FRAME PLUNGER PUMP**

**Specs**

<b>Max Flow:</b>	14 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	3000 psi
<b>Inlet Port Size:</b>	1.5
<b>Discharge Port Size:</b>	1
<b>RPM:</b>	800
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Nickel Aluminum Bronze (NAB)

**Description:**

This is a triplex [three plunger rods] positive displacement, reciprocating, plunger pump, constructed of Nickel Aluminum Bronze manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR [Buna-N] seals and o-rings. These higher capacity plunger pumps are suitable for multi-gun and multi-nozzle, high pressure systems, and pumping special liquids such as salt water. [See also 316SS Block-Style models]

**Datasheet:** [3507, 3507C, 3517, 3517C Data Sheet](#)

**Service Manual:** [35 Frame Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**



[7023.100](#)

SS Pressure Regulator

**Unloader**



[7533](#)

Multiple Gun Pressure Unloader

**Relief / Pop-Off Valve**



[7533.100](#)

SS Pressure Relief Valve

**Pressure Gauge**



[6087](#)

Pressure Gauge

**Pulsation Dampener**



[701501](#)

Pulsation Dampener-Rebuild-NBR

**Captive Acceleration Tube**



[711500](#)

Captive Acceleration Tube

**Inlet Filter**



[7108.8](#)

Inlet Filter


### Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose

### LPS Monitors



[30290](#)

LPS Monitor



[30290.120AC](#)

LPS Monitor