




**Model: [5CP2150W.3000](#)  
5CP PLUNGER PUMP - HIGH TEMP.**



**Specs**

<b>Max Flow:</b>	5 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	2000 psi
<b>Inlet Port Size:</b>	0.5
<b>Discharge Port Size:</b>	0.37
<b>RPM:</b>	1725
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

---

**Description:**

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a special W770 manifold, 304 stainless steel valve assemblies, solid ceramic plungers and standard NBR (Buna-N) o-rings and low pressure seals. High pressure seals are a special blend PTFE for high temperature applications.

**Datasheet: [5CP2120W-2140WCS-2150W Data Sheet](#)**

**Service Manual: [CP Plunger Service Manual](#)**

---

## Accessories:

### Pulsation Dampener



[6030](#)

Prrrrr-O-Lator-Rechg-FPM

### Pressure Gauge



[6097](#)

Pressure Gauge

### Relief / Pop-Off Valve



[33961S](#)

Pop-Off Valve - High Temp.

### Regulator



[7013](#)

Pressure Regulator