



The Pumps with Nine Lives

**Model: [5CP4120CSS](#)  
5CP PLUNGER PUMP**



**Specs**

<b>Max Flow:</b>	4.5 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	4000 psi
<b>Inlet Port Size:</b>	1/2"NPTF
<b>Discharge Port Size:</b>	3/8"NPTF
<b>RPM:</b>	1750
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Brass (BB)

**Description:**

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a forged brass manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. Includes side bubble gauge.

**Datasheet:** [5CP4120CSS Data Sheet](#)

**Service Manual:** [CP Plunger Service Manual](#)

**Accessories:**

Oil



[6107](#)

Crankcase Oil

Unloader



[7694](#)

Pressure Sensitive Regulating Unloader

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6089](#)

Pressure Gauge

Inlet Filter



[7104.4](#)

Inlet Filter

## Guns



[36140](#)

Gun



[36141](#)

Gun

## Bellhousing/Flex Coupling



[76215.5CP](#)

Bell Housing



[8375](#)

Flexible Coupling