



The Pumps with Nine Lives

**Model: [5CP6120](#)
5CP PLUNGER PUMP**



Specs

Max Flow:	6 gpm
Min Pressure:	100 psi
Max Pressure:	1600 psi
Inlet Port Size:	0.5
Discharge Port Size:	0.37
RPM:	1400
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a forged brass manifold, 304SS valve assemblies, solid ceramic plungers and standard NBR(Buna-N) seals and o-rings. (see also 316SS models)

Datasheet: [5CP6120-6190-6120CSSG1-6190G1 Data Sheet](#)

Service Manual: [CP Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7012](#)

Pressure Regulator

Relief / Pop-Off Valve



[33962](#)

Pop-Off Valve

Pressure Gauge



[6088](#)

Pressure Gauge

Pulsation Dampener



[6029](#)

Pmmr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7104.4](#)

Inlet Filter

Flexible Inlet Hose



[990840](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990836](#)

Flexible Discharge Hose

Other



[34334](#)

Oil Drain Kit