

Model: [6013](#)
Prrrrr-O-Lator-Rechg-FPM

Specs

Max Flow:	40 gpm
Min Pressure:	200 psi
Max Pressure:	2600 psi
Inlet Port Size:	1
Discharge Port Size:	1
Type of Accessory:	Pulsation Dampener
Material:	Stainless Steel (SS)

Description:

This valve is designed to reduce pressure fluctuations or pulsation common in all positive displacement pump systems. It must be nitrogen pre-charged prior to installation on the discharge side of the pump. It will prolong the life of the pump and system components by reducing pulsation to + or- 3%. This is constructed of 316SS with an FPM bladder for special fluid compatibility.

Accessory to be used with these Pumps:



[1851K](#) OBSOLETE 18 frame plunger pump



[3831](#) 38 FRAME BLOCK-STYLE PLUNGER PUMP



[1521](#) 25 FRAME PISTON PUMP



[2525](#) 25 FRAME PISTON PUMP



[2520C](#) 25 FRAME



PISTON PUMP

[2530.44101](#) 25 FRAME PLUNGER PUMP - TEG



[1540E.44101](#) 15 FRAME



PLUNGER PUMP - TEG
 PLUNGER PUMP - TEG

[1541.44101](#) 15 FRAME PLUNGER PUMP - TEG



[2531.44101](#) 25 FRAME