

Model: <u>6020</u>

60 FRAME PISTON PUMP



Specs

Max Flow:	60 gpm
Min Pressure:	100 psi
Max Pressure:	1000 psi
Inlet Port Size:	2
Discharge Port Size:	1.25
RPM:	500
Drive Type(s):	Belt
Material:	Brass (BB)

Description:

This is a triplex [three piston rods] positive displacement, reciprocating, piston pump, constructed with forged brass manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction.

Datasheet: 6020-6021-6040-6041 Data Sheet

Service Manual: Piston Pump Service Manual

Accessories:

Flexible Discharge Hose



990839

Flexible Discharge Hose

Flexible Inlet Hose



990843

Flexible Inlet Hose

Inlet Filter



<u>7109</u>

Inlet Filter

Captive Acceleration Tube



<u>717500</u>

Captive Acceleration Tube

Pulsation Dampener



<u>6012</u>

Prrrrr-O-Lator-Rechg-NBR

Pressure Gauge



<u>6086</u>

Pressure Gauge

Relief / Pop-Off Valve



890700

SS Regulating Relief Valve

Regulator



<u>7375</u>

SS Pressure Regulator

Oil



<u>6107</u>

Crankcase Oil