

**Model: [6040](#)**  
**60 FRAME PISTON PUMP**



**Specs**

Max Flow:	40 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	2
Discharge Port Size:	1.25
RPM:	500
Drive Type(s):	Belt
Material:	Brass (BB)

**Description:**

This is a triplex [three piston rods] positive displacement, reciprocating, piston pump, constructed with forged brass manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction.

**Datasheet:** [6020-6021-6040-6041 Data Sheet](#)

**Service Manual:** [Piston Pump Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Regulator**



[7376](#)

SS Pressure Regulator

**Unloader**



[7590](#)

Multiple Gun Pressure Unloader

**Relief / Pop-Off Valve**



[7595](#)

High Flow Relief Valve

**Pressure Gauge**



[6088](#)

Pressure Gauge

**Pulsation Dampener**



[6010](#)

Prrrr-O-Lator-Rechg-NBR

**Captive Acceleration Tube**



[714500](#)

Captive Acceleration Tube


### Inlet Filter



[7109](#)

Inlet Filter


### Flexible Inlet Hose



[990843](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990839](#)

Flexible Discharge Hose