



The Pumps with Nine Lives



**Model: [6041](#)
60 FRAME PISTON PUMP**

Specs

Max Flow:	40 gpm
Min Pressure:	100 psi
Max Pressure:	1500 psi
Inlet Port Size:	2
Discharge Port Size:	1.25
RPM:	500
Drive Type(s):	Belt
Material:	Stainless Steel (SS)

Description:

This is a triplex [three piston rods] positive displacement, reciprocating, piston pump, constructed with 316SS manifolds, 304SS valve assemblies, chrome-plated 304SS cylinders and sleeves and standard NBR [Buna-N] seals and o-rings. Its low RPM is designed for belt drive. The Uniflow design features a mechanically actuated inlet valve providing a continuous forward fluid flow and strong suction.

Datasheet: [6020-6021-6040-6041 Data Sheet](#)

Service Manual: [Piston Pump Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7376](#)

SS Pressure Regulator

Relief / Pop-Off Valve



[890711](#)

SS Pop-off Valve

Pressure Gauge



[6097](#)

Pressure Gauge

Pulsation Dampener



[6015](#)

Prrrr-O-Lator-Rechg-NBR

Captive Acceleration Tube



[714500](#)

Captive Acceleration Tube


Inlet Filter



[7109](#)

Inlet Filter


Flexible Inlet Hose



[990847](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990855](#)

Flexible Discharge Hose