



The Pumps with Nine Lives

**Model: [661D](#)
15 FRAME PLUNGER PUMP**



Specs

Max Flow:	10 gpm
Min Pressure:	100 psi
Max Pressure:	3000 psi
Inlet Port Size:	3/4"NPT(F)
Discharge Port Size:	1/2"NPT(F)
RPM:	1429
Drive Type(s):	Belt
Material:	Duplex (SSD)

Description:

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a Duplex stainless steel manifold, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. [see also block-style pumps]

Datasheet: [660-661D-661C Data Sheet](#)

Service Manual: [5-15 Frame Plunger Service Manual](#)

Accessories:

Oil



[6107](#)

Crankcase Oil

Regulator



[7013.100](#)

SS Pressure Regulator

Unloader



[7533](#)

Multiple Gun Pressure Unloader

Relief / Pop-Off Valve



[9941](#)

Pop-Off Valve



[7036](#)

SS Pressure Relief Valve

Pressure Gauge



[6087](#)

Pressure Gauge

Pulsation Dampener



[701501](#)

Pulsation Dampener-Rebuild-NBR

Captive Acceleration Tube



[711500](#)

Captive Acceleration Tube

Inlet Filter



[7105.5](#)

Inlet Filter


Flexible Inlet Hose



[990849](#)

Flexible Inlet Hose

Flexible Discharge Hose



[990852](#)

Flexible Discharge Hose

LPS Monitors



[30664](#)

LPS Monitor



[30664.120AC](#)

LPS Monitor

Other



NO IMAGE
AVAILABLE

[34334](#)

Oil Drain Kit