

**Model: [6811K](#)  
68 FRAME BLOCK-STYLE PLUNGER PUMP**



**Specs**

<b>Max Flow:</b>	15 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	5000 psi
<b>Inlet Port Size:</b>	1.5
<b>Discharge Port Size:</b>	1
<b>RPM:</b>	600
<b>Drive Type(s):</b>	Belt
<b>Material:</b>	Stainless Steel (SS)

**Description:**

This is a triplex (three plunger rods) positive displacement, reciprocating, plunger pump, constructed of a machined, 316SS block-style inlet and discharge manifolds, 316SS valve assemblies, solid ceramic plungers and standard NBR (Buna-N) seals and o-rings. These pumps are suitable for harsh liquids like saltwater and leachate, special sanitizing chemicals and food products. The K indicates the special flushed Inlet Manifold that permits an external flush liquid providing added cooling for hi-temp liquids and added lubrication for low-lubricity liquids such as DI water. Used with the 990663 Flushing Assembly, it offers containment of effluent emissions for environmental safety.

**Datasheet:** [6801-6811K Data Sheet](#)

**Service Manual:** [68 Frame Block-Style Plunger Service Manual](#)

**Accessories:**

**Oil**



[6107](#)

Crankcase Oil

**Unloader**



[7536](#)

Multiple Gun Pressure Unloader

**Relief / Pop-Off Valve**



[7037](#)

SS Pressure Relief Valve

**Pressure Gauge**



[6087](#)

Pressure Gauge

**Pulsation Dampener**



[701520](#)

Pulsation Dampener - Rebuild NBR

**Captive Acceleration Tube**



[711500](#)

Captive Acceleration Tube


**Inlet Filter**



[7106.6](#)

Inlet Filter


### Flexible Inlet Hose



[990850](#)

Flexible Inlet Hose

### Flexible Discharge Hose



[990854](#)

Flexible Discharge Hose