

Model: [701520](#)
Pulsation Dampener - Rebuild NBR



Specs

Max Flow:	15 gpm
Min Pressure:	200 psi
Max Pressure:	8300 psi
Inlet Port Size:	1/2"NPT(F)
Discharge Port Size:	1/2"NPT(F)
Type of Accessory:	Pulsation Dampener
Material:	Stainless Steel (SS)

Description:

This valve is designed to reduce pressure fluctuations or pulsation common in all positive displacement pump systems. It must be nitrogen pre-charged prior to installation on the discharge side of the pump. It is a replaceable bladder design constructed of 316SS with an NBR bladder for special fluid compatibility. It will prolong the life of the pump and system components by reducing pulsation to + or- 3%. [See also FPM version]

Accessory to be used with these Pumps:



[3501C35](#) FRAME PLUNGER PUMP



[680168](#) FRAME BLOCK-STYLE PLUNGER PUMP

[350735](#) FRAME PLUNGER PUMP



[681168](#) FRAME BLOCK-STYLE PLUNGER PUMP



[6811K68](#) FRAME BLOCK-STYLE PLUNGER PUMP



[3801K38](#) FRAME BLOCK-STYLE PLUNGER PUMP

[350135](#) FRAME PLUNGER PUMP



[380138](#) FRAME BLOCK-STYLE PLUNGER PUMP



[6801K68](#) FRAME BLOCK-STYLE PLUNGER PUMP