



The Pumps with Nine Lives



**Model:** [990833](#)  
**Flexible Discharge Hose**

**Specs**

<b>Max Flow:</b>	35 gpm
<b>Min Pressure:</b>	100 psi
<b>Max Pressure:</b>	3000 psi
<b>Inlet Port Size:</b>	1
<b>Discharge Port Size:</b>	1
<b>Type of Accessory:</b>	Flexible Discharge Hose
<b>Material:</b>	Brass (BB)

**Description:**

Flexible hose should be installed in the discharge line prior to any hard plumbing. Excessive elbows, tees and hard plumbing can cause restrictions and liquid acceleration loss and result in excessive vibration and water hammering and damage within the pump.

**Accessory to be used with these Pumps:**

[252025](#) FRAME PISTON PUMP



[2520C25 FRAME PISTON PUMP](#)

[352035 FRAME PLUNGER PUMP](#)



[353535](#) FRAME PLUNGER PUMP

[354535](#) FRAME PLUNGER PUMP

[152025](#) FRAME PISTON PUMP



**NO IMAGE  
AVAILABLE**



[2625](#) FRAME PISTON PUMP



[6024](#) OBSOLETE 60 FRAME PISTON PUMP

[3560AL](#) T35 FRAME PLUNGER PUMP

