

## Global Type A Adapter x Female NPT

## Features:

- interchanges with all products produced to A-A-59326D
- Buna seals standard
- pressure rating for adapters is based on the seal of the mating part



ASTMC38000 forged brass

Size	A380 Permanent Mold Aluminum		ASTMC38000 Forged Brass	
	Part #	Price/E	Part #	Price/E
½"	<b>G50-A-AL</b> <sup>1</sup>	<b>\$6.35</b>	<b>G50-A-BR</b> <sup>1</sup>	<b>\$11.80</b>
¾"	<b>G75-A-AL</b>	<b>5.00</b>	<b>G75-A-BR</b>	<b>10.70</b>
1"	<b>G100-A-AL</b>	<b>5.10</b>	<b>G100-A-BR</b>	<b>13.70</b>
1¼"	<b>G125-A-AL</b>	<b>7.75</b>	<b>G125-A-BR</b>	<b>17.70</b>
1½"	<b>G150-A-AL</b>	<b>5.70</b>	<b>G150-A-BR</b>	<b>20.45</b>
2"	<b>G200-A-AL</b>	<b>6.05</b>	<b>G200-A-BR</b>	<b>26.70</b>
2½"	<b>G250-A-AL</b>	<b>14.60</b>	<b>G250-A-BR</b>	<b>41.05</b>
3"	<b>G300-A-AL</b>	<b>12.40</b>	<b>G300-A-BR</b>	<b>47.05</b>
4"	<b>G400-A-AL</b>	<b>19.55</b>	<b>G400-A-BR</b>	<b>82.80</b>
5"	<b>G500-A-AL</b> <sup>1</sup>	<b>73.60</b>	<b>G500-A-BR</b> <sup>1</sup>	<b>197.30</b>
6"	<b>G600-A-AL</b>	<b>51.40</b>	---	---
8"	<b>G800-A-AL</b> <sup>1</sup>	<b>238.55</b>	---	---

Size	316 Investment Cast Stainless Steel	
	Part #	Price/E
½"	<b>G50-A-SS</b>	<b>\$18.00</b>
¾"	<b>G75-A-SS</b>	<b>19.00</b>
1"	<b>G100-A-SS</b>	<b>18.60</b>
1¼"	<b>G125-A-SS</b>	<b>29.10</b>
1½"	<b>G150-A-SS</b>	<b>31.05</b>
2"	<b>G200-A-SS</b>	<b>37.45</b>
2½"	<b>G250-A-SS</b>	<b>72.30</b>
3"	<b>G300-A-SS</b>	<b>78.35</b>
4"	<b>G400-A-SS</b>	<b>138.35</b>
6"	<b>G600-A-SS</b>	<b>248.50</b>

<sup>1</sup> Does not interchange in the ½", 5", and 8" sizes with Dixon® or Boss-Lock™ style cam & groove.