nexted

THE INDUSTRY'S FIRST CONTINUOUS DUTY FUEL TRANSFER PUMP

Cast iron pump housing

• 29 AMP / 1/3 HP Motor

• 12' Lift Capacity

- Continuous Duty for Fuel Transfer - Transfer fuel all day
- 12 to 24V DC Accepts a range of DC power
- Intelligent Tones[™] -Indicate where attention is needed
- Lower Amp Draw Save batter power and pump life • Lighter - Great for mobile tanks
- For gasoline, diesel, biodiesel up to B20, E15, kerosene, and mineral spirits



NX3210B Pump, Hose, and Nozzle

- Up to 25 GPM (95 LPM)
- 1 1/4" Inlet / 1" Outlet | 2" bung outlet
- Ultra high flow automatic nozzle | 18' hose • 20' removable power cable
- Replaceable magnetic switch
- 2 year warranty
- UL/cUL listed, ATEX, IECEx, CE certified



Pump Only w/Power Cord

- Up to 25 GPM (95 LPM)
- 1 1/4" Inlet / 1" Outlet | 2" bung outlet
- 20' removable power cable
- Replaceable magnetic switch
- 2 year warranty
- UL/cUL listed, ATEX, IECEx, CE certified
- For BSPP Threads and BSPT mounting -NX3205E (Pump Only w/Power Cord)



FR1210G Series

- Up to 15 GPM (57 LPM)
- 12V DC
- · Gasoline, diesel, E15, kerosene and B20 compatible
- 3/4" manual nozzle | 12' hose
- •8' lift capacity
- 1/4 HP motor | 30-minute duty cycle
- UL listed motor
- 2 Year Warranty
- Available in 24V DC FR2410G Arctic Duty - FR1210GARC

FR4210G Series

- Up to 20 GPM (75 LPM)
- 12V DC
- · Gasoline, diesel, E15, kerosene and B20 compatible
- 1" manual nozzle | 12' hose
- 8' lift capacity
- 1/4 HP motor | 30-minute duty cycle
- UL listed motor
- 2 year warranty
- Available in 24V DC FR4410G



RD812NH - 8 GPM RD1212NH - 12 GPM

Portable Handheld Option

- · Gasoline, diesel, biodiesel (up to B20), kerosene, and E15
- 12V DC

RTA

>

Ś

ഗ

۵

О

⋖

/230V

L

- 30-minute duty cycle
- Configurable ¾" inlet/outlet
- Aluminum construction
- Manual nozzle | 8' Discharge Hose | 6' Suction Hose
- 10' quick connect power cord with alligator clips
- UL listed motor
- Available in Pump and Cord Only RD812NN (8GPM) & RD1212NN (12GPM)

SD602G Series

- Up to 13 GPM (49 LPM)
- 115V AC
- · Gasoline, diesel, E15, kerosene and B20 compatible
- 3/4" manual nozzle | 12' hose
- •8' lift capacity
- 1/4 HP motor | 30-minute duty cycle
- UL Listed system
- 1 year warranty
- Available in 12V DC SD1202G



FR610G Series

- Up to 15 GPM (57 LPM)
- 115V AC
- Gasoline, diesel, E15, kerosene and B20 compatible
- 3/4" manual nozzle | 12' hose
- •8' lift capacity
- 1/4 HP motor | 30-minute duty cycle
- UL Listed system
- 2 year warranty



FR700V Series

- Up to 20 GPM (75 LPM)
- 115V AC
- · Gasoline, diesel, E15, kerosene and B20 compatible
- 3/4" manual nozzle | 12' Hose
- 10' (Gasoline) 12' (Diesel) lift capacity
- 1/3 HP motor | 30-minute duty cycle
- UL listed system
- 2 year warranty
- Available in 230V AC FR700VG



FR310VN Series

- •35 GPM (132 LPM)
- 115/230V AC
- · Diesel, gasoline, kerosene and B20 compatible
- 1" manual nozzle | 12' Hose
- 18' Lift Capacity
- 3/4 HP motor | 30-minute duty cycle
- UL listed system
- 2 year warranty



ALL AC PUMPS ARE UL LISTED COMPLETE SYSTEMS

FR112 Series - Rotary Pump

- 10 Gal. (37 Liters) per 100 revolutions
- Vacuum breaker

 \Box

 \Box

Z

- · Gasoline, diesel, E15, kerosene, light oils, and B20 compatible
- · Pail (FR113) or nozzle spout
- Perfect for tank or drum mounting
- UL certified
- 2 year warranty

SD62 - Rotary Pump

- 7.5 Gal. (28 Liters) per 100 revolutions
- Pail spout
- · Diesel, E15, kerosene, light oils, and B20 compatible
- · Tank or barrel mounting
- 1 year warranty

FR152 Series - Piston Pump

- 20 Gal. (75 Liters) per 100 strokes
- Vacuum Breaker
- · Gasoline, diesel, E15, kerosene, light oils and B20 compatible



Manual Nozzles

• FRHMN075S 34" | FRHMN100S 1" - gasoline, diesel

Automatic Nozzles

Standard | 2.5-14.5 GPM (9.5-55 LPM) • N075UAU10 ¾" unleaded | N075DAU10 ¾" diese

FRNA075DAU10 34" arctic diesel High flow | 5-25 GPM (19-94 LPM)

FRNA100DAU10 1" arctic diesel

Ultra high flow | 5-40 GPM (19-151 LPM)



Hose Accessories

- 34" and 1" Multiplane swivels, breakaways, and whip hoses
- UL certified

• F1810HM0 10 Micron | Up to 18 GPM (68 LPM)

Particulate

- F1810PM0 10 Micron | Up to 18 GPM (68 LPM)
- F4010PM0 10 Micron | Up to 40 GPM (151 LPM)
- F4030PM0 30 Micron | Up to 40 GPM (151 LPM)



- and B20 compatible
- Self-priming rotary vane
- 30-minute duty cycle
- Manual nozzle | 12' hose

- · Gasoline, diesel, E15, kerosene
- Self-priming rotary vane

- $\mathbf{\omega}$ • 2 year warranty

RD812NP - 8GPM*

- UL listed motor

- 10' quick connect power cord w/ alligator clips

- 115V AC | UL Listed System
- Self-priming rotary vane
- 1/3 HP motor | 30-minute duty cycle
- Diesel, gasoline, kerosene and

- 900CD digital meter



• Up to 13 GPM (49 LPM) • 12V DC | UL listed motor







FILL-RITE.












- 901C mechanical UL meter







- Up to 15 GPM (72 LPM)
- B20 compatible
- Heavy duty cast iron
- 10' (Gasoline) | 12' (Diesel) lift capacity
- 807C mechanical UL meter • 2 year warranty






- B20 compatible
- 18' lift capacity | 3/4 HP motor
- Ultra high flow nozzle | 18' hose
 - **ALL PUMPS FEATURE UL LISTED MOTORS**





ш


FR1211G













2 year warranty







• Manual nozzle | 12' hose







• Bung tank mount adapter | 8' discharge hose

- · Gasoline, diesel, E15, kerosene and
- Manual nozzle | 12' hose







• 30-minute duty cycle

2 year warranty

























• N100DAU13(Y/G) 1" gasoline, diesel, E15, biodiesel to B20, kerosene



















S ഗ • N100DAU12(G) 1" gasoline, diesel, kerosene

• 1" x 12' | 14' or 20' hose w/ static wire

• 3/4" x 15' or 1' x 20' arctic hose w/ static wire

Hydrosorb®









FILL-RITE DEF



RS

冚

둡

M MO

ш

- For DEF (diesel exhaust fluid). AdBlue, and water
- 8 GPM (30 LPM)
- Includes 3/4" straight and hose barb fittings

DF012N - 12V DC DF120N - 120V AC

Pump only

DF012CMN520 - 12V DC DF120CMN520 - 120V AC

Pump w/Hose & Nozzle

- Cage IBC bracket
- 3/4" manual nozzle
- •5' and 20' x 3/4" hose Nozzle boot
- Order DF120CAN520 for 120V AC system w/ automatic nozzle

DF012CAT520 - 12V DC DF120CAT520 - 120V AC

Pump w/Hose, Nozzle & Meter

- Cage IBC bracket
- TT10PB meter
- 3/4" automatic nozzle
- RPV (Micro Matic® composite dispense coupler)
- 5' and 20' x 3/4" Hose
- Nozzle boot

DF120DAN520 - 120V AC Pump w/Hose & Nozzle

- Drum Bracket
- 3/4" automatic nozzle
- 5' and 20' x 3/4" hose
- Nozzle hoot



• 1" FNPT ports

• 360° positioning display

• Quick, one step calibration

LCD display

- 2-20 GPM (8-75 LPM)
- Max Pressure: 120 psi
- Power: 2AA batteries
- · Measures: ounces, pints, quarts, liters, or gallons

825/825P

- 825P includes pulse output • CE certified
- +/-0.2% accuracy
- DEF, water, light oils, mild chemicals

850/850P

- 850P includes pulse output
- CF certified
- +/-0.2% accuracy
- Mass air sensor
- · DEF, water, light oils. mild chemicals



- +/- 0.5% accuracy
- Compatible with most automotive fluids (except gasoline), mild acids, very thick fluids and many industrial chemicals



• 30-minute duty cycle

- 38 psi max bypass
- Self-priming to 6' • 2 year warranty







TT10PN - 1" NPT TT10PB - 1" BSPP

TT10AN - 1" NPT

TT10AB - 1" BSPP

• Aluminum construction

kerosene, mineral spirits

• 3/4" reducer bushings

TT10ANC - 1" NPT

TT10ABC - 1" BSPP

non-potable water, jet fuel,

lavatory water, mineral spirts

• Engineered polymer construction

• 2-35 GPM (8-132 LPM)

Power: 2AA Batteries

Maximum Pressure: 50psi

Measures: Ounces, pints, quarts,

CULUSTED CE EX TECES

• +/- 1% Accuracy

liters, or gallons

· Gasoline, diesel, jet fuel, heptane,

• Nickle-plated aluminum construction

• E85, B100 bio-diesel, gasoline, diesel,

• DEF/AdBlue, antifreeze, de-icing fluid, non-potable water, other chemicals

In-line Digital Turbine Meters +/-1% ACCURACY

GLOBAL CERTIFICATIONS

EASY FIELD CALIBRATION

900CD Series

- 6-40 GPM (23-151 LPM)
- · Gasoline, diesel, BD up to B20, kerosene, E15, mineral spirits, stoddard solvents, and heptanes • Accuracy: +/- 1.25% | Repeatability: +/-0.25%
- Maximum pressure: 50 psi
- 3/4" 4-digit LCD display w/ 7-digit resettable totalizer
- Measures: English or metric plus user defined units
- ATEX, UL and cUL Listed

900CDP Series

- Includes all of the 900DB features plus: Intrinsically safe barrier & pulser included backlight display
- ATEX, UL and cUL Listed



807C Series

- 5-20 GPM (19-75 LPM)
- 3-wheel mechanical
- +/- 1% accuracy
- · Gasoline, diesel, E15, kerosene, B20, mineral spirits
- Available in 3/4" or 1" Ports
- ATEX, UL and cUL Listed

901C Series

- 6-40 GPM (23-151 LPM) • 4-wheel mechanical
- +/- 2% accuracy
- Gasoline, diesel, kerosene & mineral spirits
- Available in 1" or 1.5" ports
- ATEX, UL and cUL Listed






WHO WE ARE

In 1892, James B. Tuthill began manufacturing bricks in Chicago, Illinois, Over 120 years and five generations later, Tuthill Corporation is a global presence in vacuum pumps, blowers, plastics, and fuel and chemical transfer systems. We take great pride in our "Made in USA" moniker, making quality and durability top priorities. The Fill-Rite® and Sotera® brands stand for promises kept by doing exactly what we say for our customers, inspiring people to choose, live, and love our brand, and cultivating relationships that last for life.

To learn more visit tuthill.com

Our manufacturing facility is ISO 9001:2015 and ATEX Certified









FUEL TRANSFER SOLUTIONS



