


Model NPE Dimension Print SECTION 1

STAINLESS STEEL CLOSE-COUPLED CENTRIFUGAL PUMPS

ENGINEERING DATA

Clockwise Rotation Viewed from Drive End	Installation Drawing No. 276-81	Certified for construction purposes For Approval For Record By	
		C:	D

Signature Date



DIMENSIONS - DETERMINED BY PUMP

Pump	Suction	Discharge	HP	w	X	Y	L
1ST	11⁄4	1	1/2 - 2	35/16	43/8	2	4%16
2ST	1½	11⁄4	3/4 - 3	3¾	41/2	21/8	51/8
3ST	2	1½	1 - 3	3¾	45/8	21/8	51/8

Notes:

- 1. Pumps will be shipped with top vertical discharge as standard, for other orientations, remove casing bolts, rotate to desired position, and tighten \(\\ \\ \''\ \''\ \''\ bolts to 24 lbs.-ft.
- 2. Dimensions in inches, weight in pounds.
- 3. Not to be used for construction purposes unless certified.
- 4. Motor dimensions may vary with motor manufacturers.

AVAILABLE MOTOR WEIGHTS AND DIMENSIONS

HP	1 Phase		3 Phase		C Max. Length
	ODP	TEFC	ODP	TEFC	Length
1/2	16	21	19	18	915/16
3/4	19	24	21	21	101/4
1	22	26	23	21	11
11/2	28	35	27	27	115/16
2	33	39	32	33	121/16
3	40	43	41	37	127/16

NOTE: Dimensions in inches and weights in pounds.

Xylem Inc.

2881 East Bayard Street Ext., Suite A, Seneca Falls, NY 13148 Phone: (800) 453-6777 Fax: (888) 322-5877 www.xyleminc.com/brands/gouldswatertechnology

