

K-Kleen™

Pressure Washer Hose Assemblies

KK4PW™ Series

General Applications:

For use on pressure washers up to 4,000 PSI

Construction:

Tube – Water, hot water, detergent solutions resistant, special synthetic rubber.

Reinforcement – One or two high tensile steel wire braids.


Cover – Oil, abrasion and weather resistant special synthetic rubber, black or (blue non-marking color).


Ends – Rigid male NPT x swivel male NPT ends with bend restrictors on each end.

Service Temperature Range:

-15°F (-26°C) to +230°F (+110°C)

Branding:

Blue –  Kuriyama K-Kleen Pressure Washer Non-Marking 3/8" or 1/2" 4000 PSI (28 Mpa)

Black –  Kuriyama K-Kleen Pressure Washer 3/8" or 1/2" 4000 PSI (28 Mpa)



KK4PW-BK
Black color



KK4PW-BU
Blue color

Nominal Specifications

Part Number	Hose ID (in)	Hose OD (in)	Color	Working Pressure (psi)	Min. Bending Radius (in)	Length (ft)	Weight (lbs/each)
KK4PW06BUMMSX50	3/8	0.61	Blue	4,000	3.5	50	8.5
KK4PW06BKMSX50	3/8	0.61	Black	4,000	3.5	50	8.5
KK4PW06BUMMSX100	3/8	0.61	Blue	4,000	3.5	100	17.0
KK4PW06BKMSX100	3/8	0.61	Black	4,000	3.5	100	17.0
KK4PW08BUMMSX50	1/2	0.82	Blue	4,000	5.1	50	18.0
KK4PW08BKMSX50	1/2	0.82	Black	4,000	5.1	50	18.0
KK4PW08BUMMSX100	1/2	0.82	Blue	4,000	5.1	100	36.0
KK4PW08BKMSX100	1/2	0.82	Black	4,000	5.1	100	36.0

(3:1) Safety Factor

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.