

Redi-Lock® 300

Non-Conductive 300 PSI Push-On Hose

- **NON-CONDUCTIVE - TESTED TO ONE (1) MEGOHM PER INCH RESISTANCE MINIMUM**
- **MSHA APPROVED FLAME RESISTANT COVER**
- **EASY TO COUPLE**
- **LONG LENGTHS ON REELS**

APPLICATIONS:

- Low Pressure Pneumatic Systems
- Air Tools
- Water, Oil and Mild Chemical Solutions
- Robotic Welders

★Not recommended for unleaded gasoline

Special colors available in Blue, Gray and Red. Call for availability and or minimum run requirements.

Cover: Black Nitrile/PVC

Reinforcement: Aramid Spiral Yarn

Tube: Nitrile

Oil Resistance: RMA - Class A

Branding: REDI-LOCK NON-CONDUCTIVE

300 PSI <size> MADE IN USA MSHA1C - 114/03

Packaging: MAXIMUM 2 PCS ON REEL

1/4" - 5/8" ID hoses supplied on plastic reels, 3/4" ID hoses supplied on wooden reels



Note: For Push-On Fittings and Quick Disconnect Couplings refer to pages 13-15 of this catalog.

Service Temperature Range: -30°F (-34°C) to 180°F (+82°C)

Nominal Specifications

Part Number	Color	ID (in.)	OD (in.)	Working Pressure (PSI)	Reel Length (ft.)	Approx. Weight (lbs/pc)
REDI-LOC-04X700	Black	1/4	1/2	300	700	70
REDI-LOC-06X700	Black	3/8	5/8	300	700	91
REDI-LOC-08X700	Black	1/2	3/4	300	700	112
REDI-LOC-10X700	Black	5/8	29/32	300	700	161
REDI-LOC-12X700	Black	3/4	1 1/32	300	700	182

Note: Cut lengths for this product are available from our Kuriyama Schaumburg, IL Warehouse location. Please call (847) 755-0360 or e-mail: sales@kuriyama.com for more information.

BECAUSE WE CONTINUALLY EXAMINE WAYS TO IMPROVE OUR PRODUCTS, WE RESERVE THE RIGHT TO ALTER SPECIFICATIONS OR DISCONTINUE PRODUCTS WITHOUT PRIOR NOTICE.