### **Universal Air Hose Couplings**



#### **Zinc Plated Two Lug Hose Coupling**

| Part Number | Size<br>(in.) | Weight Each<br>(lbs.) | Standard<br>Carton |
|-------------|---------------|-----------------------|--------------------|
| HE-38       | 3/8           | 0.44                  | 25                 |
| HE-50       | 1/2           | 0.48                  | 25                 |
| HE-75       | 3/4           | 0.56                  | 25                 |
| HE-100      | 1             | 0.64                  | 25                 |



#### **Zinc Plated Four Lug Hose Coupling**

| Part Number | Size<br>(in.) | Weight Each<br>(lbs.) | Standard<br>Carton |
|-------------|---------------|-----------------------|--------------------|
| HE-125      | 1 1/4         | 1.70                  | 10                 |
| HE-150      | 1 1/2         | 1.80                  | 10                 |
| HE-200      | 2             | 2.00                  | 10                 |



# Zinc Plated Two Lug Female Threaded Coupling (NPT Threads)

|             | •             | •                     |                    |
|-------------|---------------|-----------------------|--------------------|
| Part Number | Size<br>(in.) | Weight Each<br>(lbs.) | Standard<br>Carton |
| FE-25       | 1/4           | 0.32                  | 25                 |
| FE-38       | 3/8           | 0.33                  | 25                 |
| FE-50       | 1/2           | 0.44                  | 25                 |
| FE-75       | 3/4           | 0.48                  | 25                 |
| FE-100      | 1             | 0.52                  | 25                 |



### **Zinc Plated Three Way Connector**

|             | •                     |                    |
|-------------|-----------------------|--------------------|
| Part Number | Weight Each<br>(lbs.) | Standard<br>Carton |
| TWC         | 0.90                  | 12                 |

### PSI Rating @ 70°F (+21°C)

1/4" – 2" 150 PSI



# Zinc Plated Two Lug Hose Coupling with Crimp Ferrule

| Part Number | Size<br>(in.) | Hose OD<br>(in.)  | Weight<br>Each (lbs.) | Standard<br>Carton |
|-------------|---------------|-------------------|-----------------------|--------------------|
| FHE-50      | 1/2           | 27/32 - 1 1/32    | 0.50                  | 20                 |
| FHE-75      | 3/4           | 1 1/16 - 1 11/32  | 0.60                  | 20                 |
| FHE-100     | 1             | 1 9/32 - 1 17/32  | 0.66                  | 20                 |
| FHE-101     | 1             | 1 15/32 - 1 23/32 | 0.66                  | 20                 |



### Zinc Plated Two Lug Male Threaded Coupling (NPT Threads)

| Part Number | Size<br>(in.) | Weight Each<br>(lbs.) | Standard<br>Carton |
|-------------|---------------|-----------------------|--------------------|
| ME-25       | 1/4           | 0.36                  | 25                 |
| ME-38       | 3/8           | 0.40                  | 25                 |
| ME-50       | 1/2           | 0.44                  | 25                 |
| ME-75       | 3/4           | 0.48                  | 25                 |
| ME-100      | 1             | 0.60                  | 25                 |



# Zinc Plated Four Lug Female Threaded Coupling (NPT Threads)

|  |             | •             | ,                     |                    |
|--|-------------|---------------|-----------------------|--------------------|
|  | Part Number | Size<br>(in.) | Weight Each<br>(lbs.) | Standard<br>Carton |
|  | FE-125      | 1 1/4         | 0.90                  | 10                 |
|  | FE-150      | 1 1/2         | 1.00                  | 10                 |
|  | FE-200      | 2             | 1.20                  | 10                 |



#### **Zinc Plated Blank End**

| Part Number | Weight Each<br>(lbs.) | Standard<br>Carton |
|-------------|-----------------------|--------------------|
| BE          | 0.52                  | 25                 |

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.

