

## The difference is...your margin of safety.

## NAFH-187<sup>™</sup> Type I

## Polyurethane (TPU) Lining / Filament Polyester Single Jacket

## NAFH-187™ Type I FEATURES

- Synthetic filament polyester warp and filler yarns are unaffected by the effects of mildew and rot, requiring less maintenance after use.
- The *Dura-Thane*<sup>™</sup> polyurethane inner lining is extremely strong and durable, while maintaining a lightweight and compact profile.
- Meets all requirements of the U.S. Forest Service Standard 5100-187 for Type I construction.
- · Both the hose and couplings are made in the USA.

Applications: Forestry, Wildland and CAFS Available in 50 and 100 foot lengths





Hose will be marked "450 PSI Working Pressure" in accordance with USDA Forest Service Specification 5100-187 Type I

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 100' UNCPLD
1"	NAFH-187 I	500 PSI	250 PSI	1³⁄16"	9.5 lbs.
11⁄2"	NAFH-187 I	500 PSI	250 PSI	<b>1</b> <sup>3</sup> ⁄4"	14 lbs.

NAFH-187 Type I™ and Dura-Thane™ are trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

