



NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

PR-500™

Polyurethane (TPU) Lining / Filament Polyester Single Jacket

POLY-RACK 500™ FEATURES

- Synthetic filament polyester wrap and filler yarns are unaffected by the effects of mildew and rot, requiring less maintenance after use.
- The **Dura-Thane™** polyurethane inner lining is extremely strong and durable, while maintaining a lightweight and compact profile.
- **Poly-Rack 500™** will replace unlined hose foot for foot on existing storage devices.
- It is designed for Emergency Fire Protection with water pressures not exceeding 225 PSI per NFPA 1961.
- **PR-500™** is intended to be used only with Listed hose racks, reels and cabinets where the specific combination of hose and rack, reel or cabinet has been investigated and found acceptable.
- Hose stored on racks or reels shall be protected from the weather and any local environmental condition potentially harmful to the hose.
- The hose is made and assembled in the USA. Performance shall meet and exceed NFPA 1961 Standards.



 **FAMILY OWNED
AMERICAN MADE**

Available in 50, 75 and 100 foot lengths

* Acceptance Test Pressure is 300 PSI for UL Labeled Product ** Available with factory Mutual and Underwriter's Label

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 50' UNCPLD
1½"	PR-500**	500 PSI *	250 PSI	1 11⁄16"	5 lbs.

PR-500,™ Poly-Rack 500,™ and Dura-Thane™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

