



NORTH AMERICAN FIRE HOSE

The difference is...*your* margin of safety.

Tri-Flow 600 LDH™

Polyurethane (TPU) Lining /Nylon 6-6 Double Jacket


Tri-Flow 600 LDH™ FEATURES

- Exclusive **DURA-CORD®** advanced air-textured Nylon 6-6 continuous filament warp yarns, resulting in superior toughness, abrasion resistance, cut resistance, tear strength and heat resistance when compared to competitive nylon, spun polyester or filament polyester warp constructions. **DURA-CORD®** is the registered trademark for NAFH. Fire hose sold under this brand is specifically manufactured by NAFH.
- Unique **Ultra-Shield™** high performance polymeric coating seals each and every fiber in the bundle, further improving the abrasion resistance, reducing moisture and chemical absorption, and providing vivid color-coded identification.
- The **Dura-Thane™** polyurethane inner lining is extremely light weight and compact, and is a National Sanitation Foundation (NSF 60) approved material for safely conveying drinking water.
- The **Friction Fighter System™** in **Tri-Flow 600 LDH™** creates an extremely smooth waterway surface, thereby significantly reducing friction loss and improving flow characteristics.

- With less weight and more compactness than nitrile rubber-covered single jacket reinforced hose, **Tri-Flow 600 LDH™** loads more tightly and requires less hose bed space, while at the same time providing more pressure capability, maneuverability and flexibility.
- **Tri-Flow 600 LDH™** hose is an extremely strong and flexible hose, with exceptional heat, abrasion, and chemical resistance.
- Designed to accomplish three separate fire fighting roles, including, Attack, Relay and Supply applications as defined by NFPA 1961, requiring a higher margin of safety than is possible with nitrile covered hose.
- Both the hose and couplings are made in the USA, performance shall meet and exceed NFPA 1961 standards.

Applications: Attack, Supply, Relay, High Volume CAFS and Potable Water

Available in 25, 50, 75 and 100 foot lengths



**FAMILY OWNED
AMERICAN MADE**

HOSE SIZE	SPECIFICATION NUMBER	ACCEPTANCE TEST PSI	SERVICE TEST PSI	BOWL SIZE	WEIGHT PER 100' UNCPLD
4"	TF-600-LDH	600 PSI	300 PSI	4 1 ⁷ / ₃₂ "	79 lbs.
5"	TF-600-LDH	600 PSI	300 PSI	5 1 ⁵ / ₃₂ "	91 lbs.

DURA-CORD® is a registered trademark of North American Fire Hose Corporation. All rights reserved.
TF-600 LDH,™ Tri-Flow 600 LDH,™ Ultra-Shield,™ Friction Fighter System™ and Dura-Thane™ are all trademarks of North American Fire Hose Corporation. All rights reserved.

Revision 2019A

NORTH AMERICAN FIRE HOSE

910 East Noble Way • Santa Maria, CA 93454

Tel: 805.922.7076 • Fax: 805.922.0086

NAFHC.com

