

Refrigerated Dryers - Non-cycling

i103_0617

Energy efficient non-cycling dryers



Applications

Entire shop/factory application for the elimination of water in compressed air. Must be used in applications where temperatures are above freezing.

Features/Benefits/Specs

- Vertical profile allows for minimum pressure drop and self cleans using gravitational force
- Economic initial investment that also saves costly floor space with the smallest footprint in the industry
- Units feature an open frame that provides easy access to all components
- Port sizes from 1/2" to 1 1/4"
- Max. Temp: 130° F
- Max. Inlet Temp: 20-50 SCFM: 232 PSIG
75-480 SCFM: 200 PSIG
- Pressure Dew Point: 41° F
- Required pre-filtration: 1.0 micron
- Recommended post-filtration: 0.01 micron

Part Number	Airflow (SCFM)	Pressure Drop (PSI)	Standard Voltage	Nominal Absorption Power (kW)	NPT	Height (in.)	Width (in.)	Depth (in.)	Weight (lbs.)
RDNC 0020	20	1.31	115V / 1Ph	0.21	1/2"	19	15	20	55
RDNC 0035	35	2.03	115V / 1Ph	0.29	1/2"	19	15	20	62
RDNC 0050	50	4.64	115V / 1Ph	0.30	1/2"	19	15	20	71
RDNC 0075	75	3.48	115V / 1Ph	0.45	1"	29	14	17	75
RDNC 0100	100	2.32	115V / 1Ph	0.70	1 1/4"	29	14	18	86
RDNC 0150	150	4.93	115V / 1Ph	1.00	1 1/4"	29	14	18	90

**Larger sizes available. Call factory for more information.



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTIPBE



@rti_pbe

